



KWC-No.

119602

chromeline, A 140, flexible connection hose, without pop-up valve, mains receiver, Basic, without mixing

119603

chromeline, A 140, flexible connection hose, without pop-up valve, battery, Basic, without mixing

* Automatic controled

- Dual infrared sensor A20

* Without mixing

- for cold or mixed water supply

* EcoProtect - water-saving device

* Basic: counter-sunk iqua-click

* Microprocessor-control

- flow time adjustable (1 second factory setting)

- short time off (cleaning) activatable

- continuous water flow (filling) activatable

- sensor sensitivity adjustable permanent, automatic self-calibration

- 12- or 24-hour-hygiene flushing activatable

* Fixed spout

- Neoperl® Cascade®

* OptimalSpace - ample space for washing or working

* Electrovalve

* Flexible connection hose 3/8"

* Fastening by means of stud bolt M8 x 1

* Mounting hole size ø35 mm

* Scope of delivery:

- Battery 6 V Lithium 2 CR5

- lifespan at 100 circuits/day; 4 years

3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Datos técnicos

Caudal de salida

5 l/min (3 bar)

vaciador automático

sin válvula de vaciado

Control electrónico

sin contacto

Racors

Tubo conexión flexible

caño

Fijado

IQUA-Click

3

Alimentación

Pila

Código de color

chromeline

Tipo de instalación

Standmontage

Tipo de grifo

06

Dimensión de la altura

186

Grupo de ruido

yes

Proyección A

A140

Etiqueta energética

A

Dimensión de la altura

152

Material

Latón

