



KWC-No.

121275
chromeline, A 200, B 270

121276
chromeline, A 300, B 370

Projection_A

A200/A400

A300/A400

- * Lever mixer
- * Suspension spring
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsicly safe against backflow
- * Swivel spout
 - with adjustable gland
 - Jet regulator
- * Pre-rinse spray
 - with integrated delayed closing device to minimize water hammer with valve maintenance unit for cleaning
 - SprayClean - easy to clean and actively prevents limescale

- buildup
 - SprayLock - lockable jet spray
 - PowerClean - needle spray mode
- * OptimalSpace - ample space for washing or working
- * KWC cartridge XL 46 - high capacity
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature limitation
- * Copper tubes $\varnothing 15$ mm
- * Fastening by means of threaded sleeve 1 1/4"
- * Mounting hole size $\varnothing 42$ mm

Technical Data

| | |
|-----------------------------|----------------------|
| A_Spout_Spray | 24 l/min (3 bar) |
| A_Spray (kitchen) | 15 l/min (3 bar) |
| Connection | Kupferrohranschlüsse |
| ATT-KWC-AUSLAUF | fest |
| Handling | seitenbedient |
| Kitchen_spray | Geschirrbrause |
| Projection_B | B370 |
| ATT-KWC-FARBCODE | chromeline |
| Installation_type | Standmontage |
| Faucet_typ | 01 |
| Measure_Height | 1020 |
| G_Acoustic group | 2 |
| Projection_A | A300/A400 |
| ATT-KWC-MASS-WASSERAUSTRITT | 194/275 |
| Material | Mässing |

| |
|----------------------|
| 24 l/min (3 bar) |
| 15 l/min (3 bar) |
| Kupferrohranschlüsse |
| fest |
| seitenbedient |
| Geschirrbrause |
| B370 |
| chromeline |
| Standmontage |
| 01 |
| 1020 |
| 2 |
| A300/A400 |
| 194/275 |
| Mässing |

