



KWC-No.

121281
chromeline, AD 153 +/- 8 mm, A 200, B 270

121284
chromeline, AD 153 +/- 8 mm, A 300, B 370

Projection A

A 200 / A 400

A 300

- * Lever mixer
- * Suspension spring
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsicly safe against backflow
- * Swivel spout 160°
 - with adjustable gland
 - Jet regulator
- * Pre-rinse spray
 - with integrated delayed closing device to minimize water hammer with valve maintenance unit for cleaning

- SprayClean - easy to clean and actively prevents limescale buildup
- SprayLock - lockable jet spray
- PowerClean - needle spray mode
- * OptimalSpace - ample space for washing or working
- * KWC cartridge XL 46 - high capacity
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature limitation
- * Wall connections 1/2" x 3/4", without shut-off valve L 40 eccentric 4 mm

Technical Data

Flow rate
Spray: Flow rate
Spout
Kitchenspray
Projection B
Color code
Installation type
Faucet_typ
Acoustic group
Projection A
Connection measure
Dimension Water outlet
material

34 l/min (3 bar)
15 l/min (3 bar)
fixed
Pre-rinse spray
B 370
chromeline
Wall mounted
Faucet
2
A 300
153+/-8
97/175
Brass

