

KWC-No.

121505
 stainless steel, A 235, flexible connection hoses


- * Lever mixer
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Pull-out spray
 - SprayClean - easy to clean and actively prevents limescale buildup
 - up to 700 mm pull-out length
 - SprayLock - lockable jet spray
 - PowerClean - needle spray mode, with automatic diverter reset
 - hose surface to fit faucet surface

- * Hose guide, swivelling 130°
- * EasyLock - a pull-out spray that easily slides back into place
- * KWC cartridge L 39 - universal
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature and flow rate limitation
- * Flexible connection hoses 3/8"
- * Fastening by means of threaded sleeve M33 x 1.5
- * Mounting hole size ø35 mm

Technické údaje

ATT-KWC-A_AUSZUGBRAUSE_SIEB
ATT-KWC-A_AUSZUGBRAUSE_NORMAL
Connection
ATT-KWC-AUSLAUF
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
Measure_Height
G_Acoustic group
Projection_A
EnergyLabelCH
ATT-KWC-MASS-WASSERAUSTRITT
Materiál

13 l/min (3 bar)
12 l/min (3 bar)
Flexible_Anschlussschläuche
schwenkbar
topbedient
Auszugbrause
stainless steel
Standmontage
Hebelmischer
216
I
A235
C
154
ROSTFREIER_STAHL



Náhradní díly

KWC INOX

Lever mixer - Kitchen

Modell-Linie: INOX | 10.271.033.700FL
Umyvadlové armatury | Hydraulické armatury



Cartridge L 39 - universal

536591
K:32.60.00
