



KWC-No.

121513

stainless steel, A 230, flexible connection hoses

- * Lever mixer
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Pull-out aerator
- Neoperl® Cascade®
- up to 700 mm pull-out length
- hose surface to fit faucet surface
- * Hose guide, swivelling 130°

- * EasyLock - a pull-out spray that easily slides back into place
- * KWC cartridge L 39 - universal
- with ceramic discs
- flow rate and temperature continuously variable
- temperature and flow rate limitation
- * Flexible connection hoses 3/8"
- * Fastening by means of threaded sleeve M33 x 1.5
- * Mounting hole size ø35 mm

Dane techniczne

A_Spout_Spray
Connection
ATT-KWC-AUSLAUF
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
Dimension Height
G_Acoustic group
Projection_A
EnergyLabelCH
ATT-KWC-MASS-WASSERAUSTRITT
Materiał

12 l/min (3 bar)
Flexible_Anschlusschläuche
schwenkbar
topbedient
Auszugauslauf
stainless steel
Standmontage
01
199
1
A230
C
156
ROSTFREIER_STAHL



Części zamienne



KWC INOX
Lever mixer - Kitchen

Modell-Linie: INOX | 10.271.103.700FL
Armatura umywalkowa | Armatura jednouchwytowa



Cartridge L 39 - universal

536591
K.32.60.00
