

KWC-No.

121517

stainless steel, A 230, flexible connection hoses


- * Lever mixer
- * Socket 50 mm
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Pull-out aerator
- Neoperl® Cascade®
- up to 700 mm pull-out length
- hose surface to fit faucet surface
- * Hose guide, swivelling 130°

- * EasyLock - a pull-out spray that easily slides back into place
- * OptimalSpace - ample space for washing or working
- * KWC cartridge L 39 - universal
- with ceramic discs
- flow rate and temperature continuously variable
- temperature and flow rate limitation
- * Flexible connection hoses 3/8"
- * Fastening by means of threaded sleeve M33 x 1.5
- * Mounting hole size ø35 mm

Tekniset tiedot

A_Spout_Spray
Connection
Spout
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
Measure_Height
G_Acoustic group
Projection_A
EnergyLabelCH
ATT-KWC-MASS-WASSERAUSTRITT
Materiali
IviCode

12 l/min (3 bar)
Flexible_Anschlusschläuche
schwenkbar
topbedient
Auszugauslauf
stainless steel
Standmontage
01
253
yes
A230
C
206
ROSTFREIER_STAHL
0



Varaosat

KWC INOX

Lever mixer - Kitchen

Modell-Linie: INOX | 10.271.303.700FL
Hanat | Käsi­käyt­toiset hanat



Cartridge L 39 - universal

536591

K.32.60.00
