


KWC DOMO E

Lever mixer - Kitchen

Modell-Linie: DOMO E | 10.701.003.700FL

Taps | Manual taps





KWC-No.

stainless steel, A 215, flexible connection hoses

- * Lever mixer

 * Lever installation only possible on the right side

 Child safety: cold water flow in lever position towards the front

 * gap between wall and centre of mounting hole min. 26 mm

 * TouchProtect anti-scald protection thanks to the "double skin" * Touch-rotect - anti-scala protection trianks to the aduble sk principle * Intrinsically safe against backflow * Pull-out spray - SprayClean - easy to clean and actively prevents limescale

- buildup
- up to 600 mm pull-out length
 TripleClean Normal, soft, and power stream modes
 hose surface to fit faucet surface

- QuickConnect Simple hose connection system

 * Hose guide, swivelling 150°

 * EasyLock a pull-out spray that easily slides back into place

 * OptimalSpace ample space for washing or working

 * KWC cartridge M 35 S

 with ceramic discs

- flow rate and temperature continuously variable
 temperature limitation

- * Flexible connection hoses %"

 * QuickInstallation Fastening via threaded connection with locking screws
 * Mounting hole size ø35 mm

Technical Data

Flow rate needle spray	
Flow rate normal spray	
Connection	
Spout	
Handling	
Kitchenspray	
Color code	
Installation type	
Faucet_typ	
Dimension Height	
Acoustic group	
Projection A	
Energy label	
Dimension Water outlet	
material	

8 l/min (3 bar)	
8 l/min (3 bar)	
Flexible connection hoses	
swivel	
side lever	
Pull-out spray	
stainless steel	
Pillar installation	
Lever mixer	
330	
T	
A 215	
В	
285	
stainless steel	

