

KWC AVA 2.0 Lever mixer - Basin

Modell-Linie: AVA 2.0 | 12.468.131.000FL

Taps | Manual taps



KWC-No.

125096 chromeline, A 150, flexible connection hoses, with pop-up valve

125097

chromeline, A 150, flexible connection hoses, without pop-up valve

125098

chromeline, A 150, flexible connection hoses, with Push Open

- * Lever installation only possible on the right side Child safety: cold water flow in lever position towards the front * gap between wall and centre of mounting hole min. 27 mm * EcoProtect water-saving device * Swivel court 100°
- * Swivel spout 120°
- Neoperl® Perlator® SJR, swivelling jet regulator
 * OptimalSpace ample space for washing or working
- * KWC cartridge S 25

150 27 <u>95</u> 100 67 210 -4°-16 183 ø43 max.45 🖡 M33 ø63 364 1 1/4

Pop-up_valve

with pop-up valve

without pop-up valve

with Push open

- with ceramic discs flow rate and temperature continuously variable
- * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking

- * Quickinstaliation Fastening via the screws * Mounting hole size ø35 mm * Scope of delivery: KWC pop-up valve Z.538.581.000

Technical Data

Flow rate	
Pop-up_valve	
Connection	
Spout	
Handling	
Color code	
Installation_type	
Faucet_typ	
Dimension Height	
Acoustic group	
Projection_A	
Energy Label	
Dimension Water outlet	
material	

5 l/min (3 bar)	
with pop-up valve	
Flexible connection I	hoses
swivel	
side lever	
chrome	
Pillar installation	
Basin1	
210	
Battery1	
A 150	
A	
183	
Brass	

