


KWC VITA PRO 2.0

Lever mixer - Basin

Modell-Linie: VITA PRO 2.0 | 12.528.052.000LLFL

Taps | Manual taps





KWC-No.

125228

chromeline, A 150, flexible connection hoses, with pop-up valve

125229

chromeline, A 150, flexible connection hoses, without pop-up valve

- * Lever mixer
- * Operation designed for a secure grip, as well as safe and easy
- handling
 * Ergonomic and robust operating lever, made of polyamide
- to adjust the handling even better to suit personal requirements, the offset lever can be installed so that it is twisted into the cap (standard: see illustration)
- * EcoProtect water-saving device * Fixed spout Neoperl® Perlator® laminar

Pop-up_valve

with pop-up valve

without pop-up valve

- * KWC cartridge with safety device M 35 OP
- with ceramic discs flow rate and temperature continuously variable temperature limitation
- $\mbox{\forced}$ stopper for output volume and temperature (standard
- setting)
 * Flexible connection hoses 3/8"
 * QuickInstallation Fastening via threaded connection with locking screws * Mounting hole size ø35 mm

Technical Data

| Flow rate | |
|------------------------|---|
| Pop-up_valve | |
| Connection | |
| Spout | |
| Handling | |
| Color code | |
| Installation_type | |
| Faucet_typ | |
| Dimension Height | |
| G_Acoustic group | |
| Projection_A | |
| Energy Label | |
| Dimension Water outlet | |
| material | _ |

| 5.8 l/min (3 bar) | | | |
|-------------------------|----|---|--|
| without pop-up valve | | | |
| Flexible connection hos | es | | |
| fixed | | | |
| top lever | | | |
| chrome | | | |
| Pillarinstallation | | | |
| Lever mixer | | | |
| 240 | | | |
| İ | | | |
| A 150 | | | |
| A | | | |
| 127 | | | |
| Brass | | • | |



