


## KWC IQUA

Automatic, non-contact - Basin

Modell-Linie: IQUA | 12.696.181.000

Taps | Self closing taps



### KWC-No.

#### 125277

chromeline, A 115, flexible connection hose, without pop-up valve, battery, Basic, without mixing

#### 125278

chromeline, A 115, flexible connection hose, without pop-up valve, mains receiver, Basic, without mixing

- \* Automatic controled style
- \* Infrared sensor L20
- \* Without mixing
- for cold or mixed water supply
- \* EcoProtect - water-saving device
- \* Basic: counter-sunk iqua-click
- \* Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration

### Power supply

battery

mains receiver

- 12- or 24-hour-hygiene flushing activatable
- \* Fixed spout
- Neoperl® Cascade®
- \* Electrovalve
- \* Flexible connection hose 3/8"
- \* Fastening by means of stud bolt M8 x 1
- \* Mounting hole size 53 mm
- \* Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 6 V
- 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

### Technical Data

Flow rate
pop-up valve
Electronical control
Connection
Spout
IQUA-Click
Power supply
Color code
Installation type
Faucet_typ
Measure Height
Acoustic group
Projection A
Energy label
Dimension Water outlet
material

6 l/min (3 bar)
without pop-up valve
Automatic, non-contact
Flexible connection hose
fixed
3
mains receiver
chromeline
Pillar installation
Washbasin
140
yes
A 110
A
66
Brass

