


KWC IQUA

Automatic, non-contact - Basin

Modell-Linie: IQUA | 12.696.091.000

Taps | Self closing taps



KWC-No.

125279

chromeline, A 115, flexible connection hose, without pop-up valve, battery, Basic, with mixing

125280

chromeline, A 115, flexible connection hose, without pop-up valve, mains receiver, Basic, with mixing

- * Automatic controlled style
- * Infrared sensor L10
- * With mixing
- temperature limiter adjustable
- * EcoProtect - water-saving device
- * Basic: counter-sunk iqua-click
- * Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration

Power supply

battery

mains receiver

- 12- or 24-hour-hygiene flushing activatable
- * Fixed spout
- Neoperl® Cascade®
- * Electrovalve
- * Flexible connection hoses 3/8"
- * Fastening by means of stud bolt M8 x 1
- * Mounting hole size 53 mm
- * Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6 V
- 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Technical Data

Flow rate
pop-up assembly
Electronical control
Connection
Spout
IQUA-Click
Power supply
Color code
Installation type
Faucet_typ
Dimension Height
Acoustic group
Projection A
Energy label
Dimension Water outlet
material

6 l/min (3 bar)
without pop-up valve
Automatic, non-contact
Flexible connection hose
fixed
yes
mains receiver
chromeline
Pillar installation
Washbasin
140
yes
A 110
A
66
Brass

