


KWC GASTRO E Lever mixer – Commercial kitchen

Modell-Linie: GASTRO E | 24.561.144.700FL
Taps | Dishwashing



KWC-No.

125567

stainless steel, A 200, B 270, flexible connection hoses

- * Lever mixer
- * Suspension spring
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsically safe against backflow and cross flow
- * Swivel spout
 - with adjustable gland
 - Jet regulator
- * Pre-rinse spray
 - with integrated delayed closing device to minimize water hammer
 - with valve maintenance unit for cleaning and swivelling sieve jet
 - SprayClean - easy to clean and actively prevents limescale

- buildup
 - SprayLock - lockable jet spray
 - PowerClean - needle spray mode
- * OptimalSpace - ample space for washing or working
- * KWC cartridge XL 46 - high capacity
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature limitation
- * Flexible connection hoses 1/2" with transition to 3/4"
- * Fastening by means of threaded sleeve 1 1/4"
- * Mounting hole size ø42 mm

Technical Data

Flow rate	27 l/min (3 bar)
Spray: Flow rate	15 l/min (3 bar)
Connection	flexible connection hoses
Spout	swivel
Handling	side lever
Kitchenspray	Pre-rinse spray
Projection B	B 270
Color code	stainless steel
Installation type	Pillar installation
Faucet_typ	Faucet
Dimension Height	1020
Acoustic group	2
Spray outlet: Acoustic group	yes
Projection A	A 200
Dimension Water outlet	275/194
material	stainless steel

Flow rate	27 l/min (3 bar)
Spray: Flow rate	15 l/min (3 bar)
Connection	flexible connection hoses
Spout	swivel
Handling	side lever
Kitchenspray	Pre-rinse spray
Projection B	B 270
Color code	stainless steel
Installation type	Pillar installation
Faucet_typ	Faucet
Dimension Height	1020
Acoustic group	2
Spray outlet: Acoustic group	yes
Projection A	A 200
Dimension Water outlet	275/194
material	stainless steel

NEW

