


KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL





KWC-No.

stainless steel, A 125, flexible connection hose, without drain fitting, surface-mounted power supply unit, without mixing

- * Automatic, non-contact, basin opto-electronic controlled * Made of stainless steel * Without mixing for cold or mixed water supply
- * EcoProtect water-saving device * Control electronics

- 24-hour hygiene flushing adjustable Safety shutdown in case of continuous reflection Storage of statistical data
- * Fixed spout

- Neoperl® Perlator® SSR, swivelling jet regulator * Electrovalve

- * Flexible connection hose 3/8"

 * QuickInstallation Fastening via threaded connection M33 x 1.5 with locking screws

- with locking screws

 * Mounting hole size ø35 mm


 * Scope of delivery:

 Mains receiver 100-240 V AC 6.75 V DC

 * Order separately (optional or if required):


 Possibility of parameterization via bidirectional remote control, or

 C-module (3600001331) with an app



Technical Data

Electronical control	
Connection	
Spout	
Power supply	
Color code	
nstallation type	
-aucet_typ	
Projection A	





NEW



Optional Accessories







KWC ONO E

Automatic tap, touchless – Washbasin

Modell-Linie: ONO E | 12.576.122.700FL Taps | Electronic taps

Bidirectional remote control for electronical fittings F3 and F5

2-button remote control for fittings F3 and F5

2030036654 ACEX9005

2030036849 ACEX9004