


## KWC IQUA

Automatic, non-contact - Basin

Modell-Linie: IQUA | K.12.JB.52.000N23

Taps | Self closing taps



### KWC-No.

#### 119599

chromeline, A 140, flexible connection hoses, without pop-up valve, mains receiver, Basic, with mixing

#### 119601

chromeline, A 140, flexible connection hoses, without pop-up valve, battery, Basic, with mixing

- \* Automatic controled
- Dual infrared sensor A10
- \* With mixing
- temperature limiter adjustable
- \* EcoProtect - water-saving device
- \* Basic: counter-sunk iqua-click
- \* Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration
- 12- or 24-hour-hygiene flushing activatable

- \* Fixed spout
- Neoperl® Cascade®
- \* OptimalSpace - ample space for washing or working
- \* Electrovalve
- \* Flexible connection hoses 3/8"
- \* Fastening by means of stud bolt M8 x 1
- \* Mounting hole size 63.5 mm
- \* Scope of delivery:
  - Mains receiver 100-240 V / operating voltage 6 V
  - 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

### Technical Data

Flow rate
Pop-up_valve
Electronical_control
Connection
Spout
IQUA-Click
Power_supply
Color code
Installation_type
Faucet_typ
Dimension Height
Acoustic group
Projection_A
Energy Label
Dimension Water outlet
material

5 l/min (3 bar)
without pop-up valve
Automatic, non-contact
Flexible connection hoses
fixed
Battery1
mains receiver
chrome
Pillar installation
Washbasin
186
Battery1
A 140
A
152
Brass

