



KWC-No.

119599

chromeline, A 140, flexible connection hoses, without pop-up valve, mains receiver, Basic, with mixing

119601

chromeline, A 140, flexible connection hoses, without pop-up valve, battery, Basic, with mixing

- * Automatic controled
- Dual infrared sensor A10
- * With mixing
- temperature limiter adjustable
- * EcoProtect - water-saving device
- * Basic: counter-sunk iqua-click
- * Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration
- 12- or 24-hour-hygiene flushing activatable

- * Fixed spout
- Neoperl® Cascade®
- * OptimalSpace - ample space for washing or working
- * Electrovalve
- * Flexible connection hoses 3/8"
- * Fastening by means of stud bolt M8 x 1
- * Mounting hole size 63.5 mm
- * Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6 V
 - 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

Technical Data

A_Spout_Spray	5 l/min (3 bar)
ATT-KWC-ABLAUFGARNITUR	ohne_Ablaufgarnitur
ATT-KWC-EL_STEUERUNG	berührungslos
Connection	Flexible_Anschlusschläuche
ATT-KWC-AUSLAUF	fest
ATT-KWC-IQUA_CLICK	1
ATT-KWC-STROMVERSORGUNG	Netz AP
ATT-KWC-FARBCODE	chromeline
Installation_type	Standmontage
Faucet_typ	06
Measure_Height	186
G_Acoustic_group	1
Projection_A	A140
EnergyLabelCH	A
ATT-KWC-MASS-WASSERAUSTRITT	152
Material	Mässing

