


## KWC IQUA

Automatic, non-contact - Basin

Modell-Linie: IQUA | K.12.JB.52M000B23  
Kranen | Zelfsluitende kranen



### KWC-No.

#### 119602

chromeline, A 140, flexible connection hose, without pop-up valve, mains receiver, Basic, without mixing

#### 119603

chromeline, A 140, flexible connection hose, without pop-up valve, battery, Basic, without mixing

- \* Automatic controled
- Dual infrared sensor A20
- \* Without mixing
- for cold or mixed water supply
- \* EcoProtect - water-saving device
- \* Basic: counter-sunk iqua-click
- \* Microprocessor-control
- flow time adjustable (1 second factory setting)
- short time off (cleaning) activatable
- continuous water flow (filling) activatable
- sensor sensitivity adjustable permanent, automatic self-calibration
- 12- or 24-hour-hygiene flushing activatable

- \* Fixed spout
- Neoperl® Cascade®
- \* OptimalSpace - ample space for washing or working
- \* Electrovalve
- \* Flexible connection hose 3/8"
- \* Fastening by means of stud bolt M8 x 1
- \* Mounting hole size ø35 mm
- \* Scope of delivery:
- Battery 6 V Lithium 2 CR5
- lifespan at 100 circuits/day: 4 years
- 3 Avoid using infrared controls near highly reflective surfaces (e.g. mirrors, polished stainless steel basins) as this could cause them to activate accidentally or malfunction.

### Technical Data

Doorstroomhoeveelheid	5 l/min (3 bar)
afvoergarnituur	ohne_Ablaufgarnituur
Elektronische besturing	contactloz
schroefverbindingen	Flexibele aansluitlange
uitloop	fest
IQUA-Click	3
Stroomvoorziening	Batterij
Kleurcode	chromeline
Type installatie	staande montage
Kraan type	06
Hoogteafmeting	186
geluidsklasse	yes
Projectie A	A140
Energielabel	A
Afmetingen wateruitlaat	152
Materiaal	MESSING

