



KWC-No.

121273

chromeline

- * Lever mixer
- * Suspension spring
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Intrinsically safe against backflow
- * Pre-rinse spray
 - with integrated delayed closing device to minimize water hammer
 - with valve maintenance unit for cleaning
- SprayClean - easy to clean and actively prevents limescale buildup

- SprayLock - lockable jet spray
- PowerClean - needle spray mode
- * OptimalSpace - ample space for washing or working
- * KWC cartridge XL 46 - high capacity
 - with ceramic discs
 - flow rate and temperature continuously variable
 - temperature limitation
- * Copper tubes ø15 mm
- * Fastening by means of threaded sleeve 1 3/4"
- * Mounting hole size ø42 mm

Technical Data

Spray: Flow rate	15 l/min (3 bar)
Connection	Copper tubes
Handling	side lever
Kitchenspray	Pre-rinse spray
Color code	chrome
Installation type	Pillar installation
Faucet_typ	Faucet
Measure Height	1020
Acoustic group	2
Projection A	A 400
ATT-KWC-MASS-WASSERAUSTRITT	285

Spray: Flow rate	15 l/min (3 bar)
Connection	Copper tubes
Handling	side lever
Kitchenspray	Pre-rinse spray
Color code	chrome
Installation type	Pillar installation
Faucet_typ	Faucet
Measure Height	1020
Acoustic group	2
Projection A	A 400
ATT-KWC-MASS-WASSERAUSTRITT	285

