


KWC AVA 2.0

Lever mixer - Basin - CoolFix

Modell-Linie: AVA 2.0 | 12.468.071.000FL

Taps | Manual taps





KWC-No.

125075

chromeline, A 105, flexible connection hoses, with pop-up valve

125076

chromeline, A 105, flexible connection hoses, without pop-up valv

125077

chromeline, A 105, flexible connection hoses, with Push Open

- * CoolFix Cold water flow with a centered lever
 * EcoProtect water-saving device
 * Fixed spout
 Neoperl® Perlator® SSR, swivelling jet regulator
 * KWC carticles S.25
- * KWC cartridge S 25 with ceramic discs

Pop-up_valve

with pop-up valve

without pop-up valve

with Push open

- flow rate and temperature continuously variable * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking
- screws * Mounting hole size ø35 mm

Technical Data

| Flow rate | |
|------------------------|--|
| Pop-up_valve | |
| Connection | |
| Spout | |
| Handling | |
| Color code | |
| Installation_type | |
| Faucet_typ | |
| Dimension Height | |
| Energysaving | |
| Acoustic group | |
| Projection_A | |
| Energy Label | |
| Dimension Water outlet | |
| material | |

| 5 l/min (3 bar) | |
|---------------------------|---|
| without pop-up valve | |
| Flexible connection hoses | 5 |
| fixed | |
| top lever | |
| chrome | |
| Pillar installation | |
| Faucet | |
| 163 | |
| Coolfix | |
| Battery1 | |
| A 105 | |
| A | |
| 99 | |
| Brass | |







