

KWC AVA 2.0 Lever mixer - Basin - CoolFix

Modell-Linie: AVA 2.0 | 12.468.073.000FL

Taps | Manual taps



2°-22° 237 206 145 140 ø48 max.45 M33 Ī 467 3/8"

KWC-No. 125091

pop-up valve with pop-up valve

without pop-up valve

with Push open

125092

chromeline, A 145, flexible connection hoses, without pop-up valve

chromeline, A 145, flexible connection hoses, with pop-up valve

125093

chromeline, A 145, flexible connection hoses, with Push Open

* CoolFix - Cold water flow with a centered lever
* EcoProtect - water-saving device
* Fixed spout
- Neoperl® Perlator® SSR, swivelling jet regulator
* OptimalSpace - ample space for washing or working
* KWC cartridge S 25

- with ceramic discs - flow rate and temperature continuously variable

* Flexible connection hoses %" * QuickInstallation - Fastening via threaded connection with locking

* Mounting hole size ø35 mm

Technical Data

Flow rate	
pop-up valve	
Connection	
Spout	
Handling	
Color code	
Installation type	
Faucet_typ	
Measure Height	
Energysaving	
Acoustic group	
Projection A	
Energy label	
Dimension Water outlet	
material	

5 l/min (3 bar) without pop-up valve Flexible connection hoses fixed top lever chromeline Pillar installation Faucet 206 Coolfix yes A 145 А 140 Brass

