

KWC AVA 2.0 Lever mixer - Basin

Modell-Linie: AVA 2.0 | 12.468.651.000FL

Taps | Manual taps





125096 chromeline, A 150, flexible connection hoses, with pop-up valve


125097

chromeline, A 150, flexible connection hoses, without pop-up valve

125098

chromeline, A 150, flexible connection hoses, with Push Open

- * Lever installation only possible on the right side Child safety: cold water flow in lever position towards the front * gap between wall and centre of mounting hole min. 27 mm * EcoProtect water-saving device * Swivel court 100°
- * Swivel spout 120°
- Neoperl® Perlator® SJR, swivelling jet regulator
 * OptimalSpace ample space for washing or working
- * KWC cartridge S 25



Pop-up_valve

with pop-up valve

without pop-up valve

with Push open

- with ceramic discs flow rate and temperature continuously variable
- * Flexible connection hoses %" * QuickInstallation Fastening via threaded connection with locking

- * QuickInstallation Fastening via threaded connection screws * Mounting hole size ø35 mm * Scope of delivery: KWC pop-up valve Push Open 2 in 1 Z.538.321.000

Technical Data

Flow rate	
Pop-up_valve	
Connection	
Spout	
Handling	
Color code	
Installation_type	
Faucet_typ	
Dimension Height	
Acoustic group	
Projection_A	
Energy Label	
Dimension Water outlet	
material	

5 l/min (3 bar)			
with Push oper	ı		
Flexible connec	tion hoses		
swivel			
side lever			
chrome			
Pillar installatio	on		
Faucet			
210			
Battery1			
A 150			
A			
183			

