


KWC KIO Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.000FL
Hanat | Elektroniset hanat



KWC-No.

125193
chromeline, A 220, flexible connection hoses, mains receiver

125194
matt black, A 220, flexible connection hoses, mains receiver

125195
decor steel, A 220, flexible connection hoses, mains receiver

ATT-KWC-FARBCODE

F000

F176

F127


- * IntelligentControl - electronic control
- * gap between wall and centre of mounting hole min. 26 mm
- * TouchProtect - anti-scald protection thanks to the "double skin" principle
- * Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- * Pull-out spray ergonomic spout alignment, shape and handling
- SprayClean - easy to clean and actively prevents limescale buildup
- Neoperl® Perlator® laminar
- PowerClean - needle spray mode, with automatic diverter reset
- Integrated control unit

- up to 500 mm pull-out length
- hose surface to fit faucet surface
- * Hose guide, swivelling 150°, can be extended to 360°
- * EasyLock - a pull-out spray that easily slides back into place
- * OptimalSpace - ample space for washing or working
- * KWC control unit, maintenance-free
- up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- with-out installation materials
- designed for wired connection to 1 operating unit (standard)
- * Flexible connection hoses 3/8"
- * QuickInstallation - Fastening via threaded connection with locking screws
- * Mounting hole size ø35 mm
- * Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 12 V / cable length 2000 mm
 - * To be ordered separately (optional or if necessary):
 - Swivel range limited to 120°, Z.538.320

Tekniset tiedot

EnergyLabelCH
A_Spout_Spray
ATT-KWC-EL_STEUERUNG
ATT-KWC-LICHT
Connection
Spout
ATT-KWC-STROMVERSORGUNG
Handling
Kitchen_spray
ATT-KWC-FARBCODE
Installation_type
Faucet_typ
ATT-KWC-BAUFORM
Measure_Height

B
10 l/min (3 bar)
yes
2
04
2
2
3
yes
F000
yes
01
3
362





KWC KIO
Kitchen - with LED-technology

Modell-Linie: KIO | 10.481.232.000FL
Hanat | Elektroniset hanat

G_Acoustic_group	yes
Projection_A	A220
IviCode	0