


KWC

PROTRONIC-S electronic pillar mixer with battery operation

Modell-Linie: PROTRONIC-S | AQUA130 Taps | Electronic taps





KWC-No.

2000067773

PROTRONIC-S battery-supplied washbasin mixer with touch-free operation, DN 15 with aerator and integrated flow control, for connection to hot and cold water supply, polished chromium-plated

brass. With temperature selection lever and conversion set for concealed mixing device, 6 V battery.

Technical Data

with backflow preventer	yes
calculation flow rate cold wat	0.07 l/s
calculation flow rate hot wate	0.07 l/s
default automatic hygiene flus	not activated
default flow time	60 Seconds
depressurised	no
with filter	yes
functional principle	electronic self-closing
hygiene flushing	yes
diameter nominal	DN 15
inlet size	G 3/8
Locking mechanism	Top section, non-ceramic
material fitting	brass
minimum flow pressure	1 bar
type of mixing	yes
number of batteries	1
Parameterization	remote control
Pop-up waste set	no
power supply connection	Battery 6 V
position of power connection	from bottom
Type of power supply	Battery
protective system IP	IP65
with rosettes/cover plate	no
protective shutdown	yes
sound insulation	no
Spout	fixed





кwс

PROTRONIC-S electronic pillar mixer with battery operation

Modell-Linie: PROTRONIC-S | AQUA130 Taps | Electronic taps

spout projection	102 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	no	
with transformer/power supply	no	
type of batteries	CR-P2 Lithium battery 6V	
type of mounting	tap hole	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	pillartap	
volume flow rate at 3 bar	0.1 l/s	
water connection	hose (gland nut)	
Accent colour	none	
Basic colour	chrome-look (glossy)	

Optional Accessories







PURETHERM under-table thermostat

2030012758	
PURE0031	

Remote control **2000101087** ZAQUA091

Aerator

2000101160	
ZAQUA087	