


KWC AQUAFIX

Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002

Installation frames | Installation units urinals





KWC-No.

2000110549

Installation frame for stainless steel urinals with flush valve for in-wall installation

AQUAFIX installation frame for stainless steel urinals, with fully assembled basic installation kit for in-wall urinal flush valves, manually operated or touch-free, opto-electronically controlled. Self-supporting, powder-coated, steel frame construction, TÜV tested, for installation of single units in dry-wall lining, adjustable height fixing as well as tap connection and outlet mount, sound-insulated wall duct with G 1/2, universal outlet bend DN 50, urinal fixing bolts, building protection and fixing materials.

Dimensions 525 x 1440 mm (W x H)

Technical	Data

application	urinals	
barrier-free	No	
Built-in fitting model	Built-in section	
height adjustment	200 mm	
diameter nominal	DN 15	
material	steel	
minimum wall thickness	135 mm	
type of mixing	No	
outlet size	DN 50	
overall depth	135 mm	
overall height	1,440 mm	
overall width	525 mm	
position of power connection	from side	
type	installation element	
type of mounting	wall and floor mounting	

Mandatory Accessories



KWC AQUAFIX Installation frame with flush valve for in-wall installation for stainless steel urinals

Modell-Linie: AQUAFIX | AQFX0002 Installation frames | Installation units urinals



F5E electronic urinal flush valve for inwall installation

2030067743	
F5EF3010	

Optional Accessories



AQUAFIX wall bracket

2000100867 ZCMPX140