


KWC AQUAFIX

Urinal installation frame for stainless steel urinals with siphon control

Modell-Linie: AQUAFIX | CMPX136

Installation frames | Installation units urinals



KW C-No.

2030020069

Installation frame for urinals with trap control

AQUAFIX urinal installation frame for stainless steel urinals with siphon control, self-supporting powder coated steel frame construction, TÜV-tested, for individual mounting for dry-wall lining, height adjustable fastening of objects, height adjustable fitting connection and outlet mount, premounted for KWC urinal CMPX538.

sound-insulated wall duct G 1/2, universal outlet bend DN 50, urinal fastening bolts, building protection and fixing material.

Dimensions 525 x 1120 mm (W x H)

Technical Data

application	urinal flush valve
barrier-free	No
Built-in fitting model	Built-in section
height adjustment	200 mm
diameter nominal	DN 15
material	steel
minimum wall thickness	135 mm
type of mixing	No
outlet size	DN 50
overall depth	135 mm
overall height	1,120 mm
overall width	525 mm
type	installation element
type of mounting	wall and floor mounting

Optional Accessories





KWC AQUAFIX
Urinal installation frame for stainless steel urinals with siphon control

Modell-Linie: AQUAFIX | CMPX136
Installation frames | Installation units urinals

AQUAFIX wall bracket

2000100867
ZCMPX140