


KWC AQUAFIX

Installation frame for WC pan, with wall-installation cistern

Modell-Linie: AQUAFIX | AQFX0006

Installation frames | Installation units wc





KWC-No.

2030020126

 $In stallation \, frame \, for \, WC \, pan, \, with \, wall-in stallation \, cistern$

AQUAFIX installation element for wall-mounted toilet bowl, with wall-installation cistem. Self-supporting, powder coated steel-frame construction, TÜV tested, for individual mounting for dry-wall lining. Concealed toilet cistern with water condensation insulation, with dual-volume flushing (7,5-4,5 l or 4-2 l) or Start/Stop flushing, triggering function transferred via flexible pressure spirals, charge

valve noise group I, mounting bracket 4-fold adjustable for toilet-connecting elbow DN 90 / DN 100, complete with flexible connecting hose, toilet-connecting elbow, retaining bolts for toilet, building protection and fastening material.

Dimensions 450 x 1120 mm (W x H)

Technical Data

application	WC flush v
barrier-free	no
Built-in fitting model	Built-in sec
height adjustment	200 mm
diameter nominal	DN 15
material	steel
minimum wall thickness	155 mm
type of mixing	no
outlet size	DN 100
overall depth	155 mm
overall height	1,120 mm
overall width	450 mm
type	installation
type of mounting	wall and flo

WC flush valve
no
Built-in section
200 mm
DN 15
steel
155 mm
no
DN 100
155 mm
1,120 mm
450 mm
installation element
wall and floor mounting

Mandatory Accessories



KWC AQUAFIX

Installation frame for WC pan, with wall-installation cistern

Modell-Linie: AQUAFIX | AQFX0006 Installation frames | Installation units wo











Flushing plate with 1 button for wall-installation cistern

2000067429 AQUA557

Flushing plate with 2 buttons for wall-installation cistern

2000067493 AQUA555

EXOS. - A3000 open electronic WC controller for cistern

2030036621 EXOS0027

AQUATIMER - A3000 open electronic WC controller for cistern

2030021142 AT300051

Optional Accessories



AQUAFIX wall bracket

2000100867