

KWC PROTRONIC-S


Electronic pillar mixer with plug-in power supply unit

Modell-Linie: PROTRONIC-S | PRTRS0009

Taps | Electronic taps







KWC-No.

2030025078

PROTRONIC-S mains-supplied washbasin mixer with touch-free operation, DN 15 with aerator and integrated flow control, for connection to hot and cold water supply, polished chromium-plated

brass. With temperature selection lever, conversion set for concealed mixing device and plug-in power supply with EU male connector, 230 V AC.

Technical Data

| with backflow preventer | Yes |
|--------------------------------|--------------------------|
| calculation flow rate cold wat | 0.07 l/s |
| calculation flow rate hot wate | 0.07 l/s |
| default automatic hygiene flus | not activated |
| default flow time | 60 Seconds |
| depressurised | No |
| with filter | Yes |
| functional principle | electronic self-closing |
| hygiene flushing | Yes |
| diameter nominal | DN 15 |
| inlet size | G 3/8 |
| Locking mechanism | Top section, non-ceramic |
| material fitting | brass-look |
| minimum flow pressure | 1 bar |
| type of mixing | Yes |
| Parameterization | remote control |
| Pop-up waste set | No |
| power supply connection | 230 VAC |
| position of power connection | from bottom |
| Type of power supply | Transformer |
| protective system IP | IP55/22 |
| with rosettes/cover plate | No |
| protective shutdown | Yes |
| sound insulation | No |
| Spout | fixed |
| spout projection | 102 mm |





KWC PROTRONIC-S

Electronic pillar mixer with plug-in power supply unit

Modell-Linie: PROTRONIC-S | PRTRS0009

Taps | Electronic taps


| surface finish fitting | chromed | |
|-------------------------------|------------------------|--|
| surface treatment fitting | polished | |
| temperature limit | Yes | |
| thermal disinfection | No | |
| with transformer/power supply | Yes | |
| type of mounting | tap hole | |
| type of operation | sensor operation | |
| type of sensor | opto-electronic sensor | |
| type of tap | pillar tap | |
| volume flow rate at 3 bar | 0.1 l/s | |
| water connection | hose (gland nut) | |
| Accent colour | none | |
| Basic colour | chrome-look (glossy) | |

Optional Accessories









Remote control

Aerator

2000101087 ZAQUA091

2000101160 ZAQUA087

PURETHERM under-table thermostat

2030012758 PURE0031

Extension cable 5 m

2030043814 ACEX9010

Spare Parts







2000104691 ASXX1015



2000109491 EPRTR0029



Spare part set

2000105106 EPRTR0009



Plug-in power supply unit

2030039823 ACEX9002