


## **KWC**

F3E electronic pillar tap with in-wall power supply

### Modell-Linie: F3E | F3EV1008

Taps | Electronic taps





### KWC-No.

#### 2030033544

#### 2030039464

with flow regulator 3.0 l/min

F3E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve cartridge and sensor in all-metal housing, high-polished chromium-plated brass. Aerator with integrated flow regulator 3.0 l/min. Activated water hygiene

### volume flow rate at 3 bar

0.1 1/9

0.05 l/s

flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control. With in-wall power supply 100 - 240 V AC.

# Technical Data

lechnical Data	
with backflow preventer	
calculation flow rate cold wat	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
Parameterization	
Pop-up waste set	
power supply connection	
position of power connection	
power consumption	
Type of power supply	
protective system IP	
with rosettes/cover plate	
protective shutdown	
sound insulation	

no	
0.1 l/s	
no	
24h after the last activity	
no	
yes	
electronic self-closing	
yes	
DN 15	
G 3/8	
Top section, non-ceramic	
brass	
1 bar	
no	
remote control	
no	
100 - 240 V AC	
from bottom	
1.5 Voltampere	
Transformer	
IP59K	
no	
yes	
no	









## **KWC**

F3E electronic pillar tap with in-wall power supply

# Modell-Linie: F3E | F3EV1008 Taps | Electronic taps


Spout	fixed	
spout projection	100 mm	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	no	
thermal disinfection	no	
with transformer/power supply	yes	
type of mounting	tap hole	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	pillar tap	
volume flow rate at 3 bar	0.05 <i>V</i> s	
water connection	hose (gland nut)	
Accent colour	none	
Basic colour	chrome-look (glossy)	

### **Optional Accessories**









Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005

2-button remote control for fittings F3 and F5

**2030036849** ACEX9004

PURETHERM under-table thermostat

**2030012758** PURE0031

Extension cable 5 m

**2030043814** ACEX9010

# **Spare Parts**







Solenoid valve cartridge

2030045522

3.0 I/min. aerator

2030041424

In-wall power supply

2030039825



# KWC

F3E electronic pillar tap with in-wall power supply

Modell-Linie: F3E | F3EV1008 Taps | Electronic taps

ACXX9002	ASXX1008	ACEX9003