

Modell-Linie: F5S | F5ST2009

Showers | Self closing showers





KWC-No.

2030040291

F5S-Therm self-closing thermostatic wall-mounted mixer DN 15 for wall mounting, for shower facilities. Hydraulically controlled, connects to hot and cold water. With a pre-assembled hygiene unit including sensor with control electronics and 6 V lithium battery (CR-P2) for performing an automatic water hygiene flushing and storage of statistical data. FRAMIC self-closing cartridge, hydraulically controlled, low-maintenance and stagnation-free, with ceramic disc technology, self-closing, flow pressure-independent due to medium separated design. Stepless adjustment of flow duration. Thermostat with metal handle with adjustable and tum-proof temperature stop, with the option for a manual thermal disinfection. Scald-protected Safe-Touch housing with outlet on top, G 3/4 B, for installation of bent outlet or wall-mounted shower pipe. All-metal construction, high-polished chromium-plated brass. With adjustable and turn-proof connections with backflow preventer and strainers, completely covered with depth-adjustable screw rosettes. Activated water hygiene flushing, fixed interval of 24 hours. With option for parameterization and communication via optional, bidirectional remote control.

Technical Data

additional connections	
with backflow preventer	
calculation flow rate cold wat	
calculation flow rate hot wate	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	
type of mixing	
number of batteries	

no		
yes		
0.15 l/s		
0.15 l/s		
no		
no		
not possible		
fixed interval 24 hour	5	
yes		
yes		
hydraulic self-closing		
no		
yes		
DN 15		
G 1/2 B		
Top section, ceramic		
brass-look		
35 Seconds		
1 bar		
5 Seconds		
with thermostat		
1		





Modell-Linie: F5S | F5ST2009 Showers | Self closing showers

Parameterization	remote control	
power supply connection	Battery 6 V	
power consumption	1.5 Voltampere	
Type of power supply	Battery	
protective system IP	IP59K	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	no	
sound insulation	no	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	manual	
with transformer/power supply	no	
type of batteries	CR-P2 Lithium battery 6V	
type of mounting	wall mounting	
type of operation	manual operation	
type of sensor	opto-electronic sensor	
type of shower	wall fitting	
volume flow rate at 3 bar	0.2 V/s	
water connection	S-connections	
position of water connection	from backside	
Accent colour	none	
Basic colour	chrome-look (glossy)	

Optional Accessories

Bent outlet

2030050434 ACXX2005









Bent outlet	Shower pipe	AQUAJ
2030050435	2030041522	20001
ACXX2006	ACSX2002	AOUA

AJET-Slimline shower head

103757 A757



Modell-Linie: F5S | F5ST2009

Showers | Self closing showers





AQUAJET-Comfort shower head

2030021283 SHAC0008 Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005 2-button remote control for fittings F3 and F5

2030036849 ACEX9004

Spare Parts







Temperature stop

2030003296 EAQLT0003



Plug chromed

2030053006 ASSX9004



Thermocouple

2030003300 EAQLT0004



Push cap

2030050542 ASST9001

2030003258 EAQLT0002

Cover





Temperature handle

2030050541

ASXT9004

Screw rosette

2030046777 ASXX9003 Mounting set

2030003401 EAQLT0009



Modell-Linie: F5S | F5ST2009 Showers | Self closing showers





2030048357 ASSX9003





FRAMIC Self-closing cartridge

ge F5 Foil

2030053034 ASET2010



Solenoid valve cartridge

2030045522 ACXX9002



Battery compartment

3600002063 ACEX9023





2030041485 ASLM9001 Hygiene unit for F5S-Therm

2030041162 ACST9001



Hexagonal socket wrench

2030047722 ACEX9011

2030046145 ASSX9001

##