

**KWC-No.**

**2030041523**

Moduł higieniczny do F5S-Mix

Hygiene unit for F5S-Therm self-closing thermostatic mixer for in-wall installation for shower facilities, for performing of automatic hygiene flushing and program-controlled thermal disinfection (additional bypass solenoid cartridge necessary) and storage of statistical data. Stainless steel cover plate 190 x 245 mm including

sensor with control electronics and 6 V lithium battery (CR-P2) as well as solenoid valve cartridge. Activated water hygiene flushing (30 s), fixed interval time 24 hours and saving of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

**Dane techniczne**

Liczba baterii	1
Pojemność	1
Ilość uom	Sztuki
Rodzaje baterii	CR-P2

1
1
Sztuki
CR-P2

**Akcesoria opcjonalne**



**Dwukierunkowy pilot do armatury F3 i F5**

**2030036654**  
ACEX9005

**Pilot 2-przyciskowy do armatury F3 i F5**

**2030036849**  
ACEX9004

**Kartusz z zaworem elektromagnetycznym**

**2030003033**  
EAQFU0001

**Kartusz z zaworem elektromagnetycznym**

**2030045522**  
ACXX9002


**Części zamienne**

## KWC

Moduł higieniczny do F5S-Mix


Modell-Linie: F5 | ACST2001

Armatura natryskowa | Wyposażenie dodatkowe do armatur natryskowych



Panel ze stali szlachetnej

**2030049948**  
ASST2002




Kartusz z zaworem elektromagnetycznym

**2030045522**  
ACXX9002



Bateria litowa 6V

**2000104846**  
EPRTR0008



Czujnik, ID 81/00001

**2030041484**  
ASLM2001