


KWC F5L-Therm Thermostatic single-lever pillar mixer

Modell-Linie: F5L | F5LT1001

Taps | Manual taps





KWC-No.

2030066480

F5L-Therm thermostatic single-lever mixer as DN 15 pillar mixer for sanitary facilities. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and tum-proof temperature stop, and ceramic disc technology. With mechanism for optional hygiene unit for automatic hygiene flushing, program-controlled thermal disinfection and storage of statistical data. For connection to hot water and cold water via hoses, includes strainers. All-metal construction, highpolished chrome-plated brass. Anti-theft aerator, slim design, with integrated flow rate controller 5.0 l/min, projection 100 mm.

Technical Data

with backflow preventer	no
depressurised	no
with filter	yes
functional principle	manual
hygiene flushing	prepared
dia meter nominal	DN 15
inlet size	G 3/8
Locking mechanism	Top section, o
material fitting	brass
minimum flow pressure	1 bar
type of mixing	with thermos
Pop-up waste set	no
with rosettes/cover plate	no
sound insulation	no
Spout	fixed
spout projection	100 mm
surface finish fitting	chromed
surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
type of mounting	tap hole
type of operation	manual oper
type of tap	pillartap
volume flow rate at 3 bar	0.08 l/s
water connection	hose (gland r

no				
no				
yes				
manual				
prepared				
DN 15				
G 3/8				
Top section, ce	eramic			
brass				
1 bar				
with thermosto	at			
no				
no				
no				
fixed				
100 mm				
chromed				
polished				
yes				
yes				
tap hole				
manual opera	tion			
pillar tap				
0.08 l/s				
hose (gland ni	ut)			





KWC F5L-Therm Thermostatic single-lever pillar mixer

Modell-Linie: F5L | F5LT1001

Taps | Manual taps

Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories









Socket for F5L single-lever pillar mixer

Anti-twist protection

5.0 l/min aerator, angle-adjustable

2030041326 ACXX1002

Hygiene unit for F5L single-lever mixers

2030068985 ACLX1001



Hygiene unit for in-wall installation for F5L single lever mixers

2030068987 ACLX1005

2030041325 ACLM1010

Spare Parts



Mounting key



KWC F5L-Therm Thermostatic single-lever pillar mixer

Modell-Linie: F5L | F5LT1001 Taps | Manual taps

2030041329 ACXX1003