


KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT1004

Taps | Manual taps





KWC-No.

2030066484 Projection 215 mm

2030066483

2030066486 Projection 275 mm

F5L-Therm thermostatic single-lever mixer as DN 15 wall-mounted mixer for wall mounting with lockable swivelling spout, for sanitary facilities. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. With mechanism for optional hygiene unit for automatic hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge

spout projection

215 mm

155 mm

275 mm

necessary) and storage of statistical data. For connection to hot and cold water. Scald-protected, safe-touch housing, all-metal construction, high-polished chrome-plated brass. Laminar jet controller with integrated flow rate controller 6.0 l/min. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. Projection 155 mm.

Technical Data

Technical Data	
with backflow preventer	yes
depressurised	no
with filter	yes
functional principle	manual
hygiene flushing	prepared
diameter nominal	DN 15
inlet size	G 1/2 B
Locking mechanism	Top section
material fitting	brass
minimum flow pressure	1 bar
type of mixing	with thern
Pop-up waste set	no
with rosettes/cover plate	yes
protective shutdown	no
sound insulation	no
Spout	rotating, b
spout projection	155 mm
surface finish casing	chromed
surface finish fitting	chromed
surface treatment fitting	polished

yes	
no	
yes	
manual	
prepared	
DN 15	
G 1/2 B	
Top section, ceramic	
brass	
1 bar	
with thermostat	
no	
yes	
no	
no	
rotating, bottom	
155 mm	
chromed	
chromed	
polished	



KWC F5L-Therm

Thermostatic single-lever wall-mounted mixer

Modell-Linie: F5L | F5LT1004

Taps | Manual taps

temperature limit	yes
thermal disinfection	yes
type of mounting	wall mounting
type of operation	manual operation
type of tap	bib tap
volume flow rate at 3 bar	0.1 l/s
water connection	S-unions
Accent colour	none
Basic colour	chrome-look (glossy)

Optional Accessories





Hygiene unit for F5L single-lever wall mixers

2030039446 ACLM9001

mixers

Theft-proof housing for aerator

2000104778 ZTAPS0005

Spare Parts









Swivel spout, 160 mm

2030032815 ASXX1002 Laminar jet regulator

2030012352 ETAPS0037 Mounting set

2030003401 EAQLT0009 Screw rosette

2030046777 ASXX9003