


KWC F5L-Therm thermostatic single-lever in-wall mixer

Modell-Linie: F5L | F5LT2005
Showers | Manual shower



KWC-No.

2030066500

F5L-Therm thermostatic single-lever mixer DN 15 as finished installation kit for in-wall installation in basic installation kit, for shower facilities. For connection to hot and cold water. Function block with integrated thermostatic cartridge and mechanism for an optional hygiene unit for automatic hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid valve cartridge necessary) and storage of statistical data.

Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. All-metal construction, visible parts high-polished, chrome-plated. Holding frame including profile seal, stainless-steel cover plate 190 x 245 mm with covered screw fixing, chrome-plated plastic rosette, backflow preventer and strainers. Depth adjustability 25 mm.

Technical Data

additional connections

no

with backflow preventer

yes

Built-in fitting model

Finishing section

circulation

no

connection with pay water disp

not possible

Cover plate height

245 mm

Cover plate width

190 mm

with filter

yes

functional principle

manual

for hand shower

no

hygiene flushing

prepared

diameter nominal

DN 15

inlet size

G 3/4 B

Locking mechanism

Top section, ceramic

material casing

stainless steel

material fitting

brass

minimum flow pressure

1 bar

type of mixing

with thermostat

with rosettes/cover plate

yes

protective shutdown

no

shower pipe draining

no

sound insulation

no

surface finish casing

satin finished

surface finish fitting

chromed




KWC

F5L-Therm thermostatic single-lever in-wall mixer

Modell-Linie: F5L | F5LT2005
Showers | Manual shower

surface treatment fitting	polished
temperature limit	yes
thermal disinfection	yes
with transformer/power supply	no
type of mounting	in-wall installation with box
type of operation	manual operation
type of shower	in-wall fitting
volume flow rate at 3 bar	0.23 l/s
water connection	threaded connection (external)
position of water connection	from side
Accent colour	chrome-look (glossy)
Basic colour	stainless steel


Mandatory Accessories



R5 System box for in-wall mixer


2030028990
F5BX2001

Optional Accessories



Extension set for F5L DN 15 single lever mixer

2030044779
ACLM2002



Hygiene unit for F5L single-lever in-wall mixer


2030041526
ACLM2001

Spare Parts

KWC


F5L-Therm thermostatic single-lever in-wall mixer

Modell-Linie: F5L | F5LT2005
Showers | Manual shower




Rosette

2030048765
ASET2006



Cover plate stainless steel

2030045475
ASXM2001



Holding frame

2030045472
ASXX9004



Stainless steel care set

2000109019
ZWSPL0024




Cleaning product CHROMOL

2000105091
ZWSPL0023



Backflow preventer DN 6

2030045816
ASXX9002



Spare part set

2030045818
ASLM2005