


Modell-Linie: F5L | F5LT2020

Showers | Manual shower





KWC-No.

2030066509

F5L-Therm stainless-steel shower panel for wall mounting with single-lever thermostat DN 15 and connecting nozzle for shower head. For connection to hot and cold water. Function block with integrated mixing cartridge and pre-assembled hygiene unit including sensor with control electronics to perform automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass so lenoid-operated flush valve cartridge necessary) and storage of statistical data. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. All-metal construction, visible parts high-polished, chrome-plated. Connecting nozzles for separate required DN 15 KWC shower head with pre-fitted flow regulator 9.0

l/min. Stainless steel housing with raised function surface and cover caps made of plastic. With adjustable and lockable connections with backflow preventer and strainers. Activated hygiene flushing, fixed interval of 24 hours. With option for parameterization and communication via optional, bidirectional remote control. Optional hygiene unit for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via plug-in power supply unit 6.75 V/12 V DC.

Housing dimensions $235 \times 1160 \times 90 \text{ mm}$ (W x H x D)

Shower head and battery compartment including battery or power supply unit with extension cable must be ordered separately.

Technical Data

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
minimum flow pressure	
type of mixing	
overall depth	
overall height	

no
yes
no
no
not possible
fixed interval 24 hours
yes
no
manual
no
yes
DN 15
G 1/2 A
Top section, ceramic
stainless steel
1.4301 Chrome Nickel steel V2A
brass-look
1 bar
with thermostat
90 mm
1,160 mm











Modell-Linie: F5L | F5LT2020 Showers | Manual shower

overall width	235 mm	
Parameterization	remote control	
power supply connection	6,75 / 12 V DC	
position of power connection	from top / backside	
Type of power supply	Other	
with rosettes/cover plate	yes	
protective shutdown	no	
shower pipe draining	no	
Shower head	for separately shower head	
with shower set	no	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	yes	
with transformer/power supply	no	
type of mounting	wall mounting	
type of operation	manual operation	
type of sensor	opto-electronic sensor	
type of shower	shower panel	
volume flow rate at 3 bar	0.15 l/s	
water connection	hose (gland nut)	
position of water connection	from top / backside	
with soap dish	no	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel-look	

Mandatory Accessories









AQUAJET-Slimline shower head for KWC shower panels and systems

2030054255 SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

2030054254 SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

2030054793 SHMU0011


Battery compartment

3600002063 ACEX9023



Modell-Linie: F5L | F5LT2020 Showers | Manual shower





Power supply unit

2030039477 ACEX9001

Extension cable 5 m

2030043814 ACEX9010

Optional Accessories









Flow controller 6.0 I/min

2030027586 ESHHE0004 Flow controller 12.0 I/min

2000104783 ESHHE0002 Solenoid valve cartridge


2030003033 EAQFU0001 Shower gel dish for F5 shower panels made of stainless steel

2030057077 ACXX2021









Housing extension for F5 shower panels made of stainless steel

2030057066 ACXX2011 Housing extension for F5 shower panels made of stainless steel


2030057067 ACXX2012 Housing extension for F5 shower panels made of stainless steel

2030057068 ACXX2013 Housing extension for F5 shower panels made of stainless steel

2030057069 ACXX2014



Modell-Linie: F5L | F5LT2020 Showers | Manual shower







Housing extension for F5 shower panels made of stainless steel

2030057070 ACXX2015

2-button remote control for fittings F3 and F5

2030036849 ACEX9004

Bidirectional remote control for electronical fittings F3 and F5

2030036654 ACEX9005

Spare Parts





Stainless steel care set

2000109019 ZWSPL0024

Rosette

2030048765 ASET2006