


### Modell-Linie: F5L | F5LT2022

Showers | Manual shower





### KWC-No.

#### 2030066541

F5L-Therm stainless-steel shower panel for wall mounting with single-lever thermostat DN 15 and connecting nozzle for shower head. For connection to hot and cold water. Function block with integrated mixing cartridge and mechanism for an optional water hygiene unit for automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and tumproof temperature stop, and ceramic disc technology. All-metal

construction, visible parts high-polished, chrome-plated. Connecting nozzles for separate required DN 15 KWC shower head with prefitted flow regulator 9.0 l/min. Stainless steel housing with raised function surface and cover caps made of plastic. With adjustable and lockable connections with backflow preventer and strainers.

Housing dimensions  $235 \times 1160 \times 90 \text{ mm}$  (W x H x D)

Shower head must be ordered separately.

### Technical Data

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
minimum flow pressure	
type of mixing	
overall depth	
overall height	
overall width	
with rosettes/cover plate	

no
yes
no
no
not possible
yes
no
manual
no
prepared
DN 15
G 1/2 A
Top section, ceramic
stainless steel
1.4301 Chrome Nickel steel V2A
brass-look
1 bar
with thermostat
90 mm
1,160 mm
235 mm
yes





# **Modell-Linie: F5L | F5LT2022** Showers | Manual shower

protective shutdown	no			
shower pipe draining	no			
Shower head	for separately shower head			
with shower set	no			
sound insulation	no			
surface finish casing	satinfinished			
surface finish fitting	chromed			
surface treatment fitting	polished			
temperature limit	yes			
thermal disinfection	yes			
type of mounting	wall mounting			
type of operation	manual operation			
type of shower	shower panel			
volume flow rate at 3 bar	0.15 l/s			
water connection	hose (gland nut)			
position of water connection	from top / backside			
with soap dish	no			
Accent colour	chrome-look (glossy)			
Basic colour	stainless steel-look			

## **Mandatory Accessories**







AQUAJET-Slimline shower head for KWC shower panels and systems

**2030054255** SHAS0011

AQUAJET-Comfort shower head for KWC shower panels and systems

**2030054254** SHAC0011

MÜNCHEN shower head for KWC shower panels and systems

**2030054793** SHMU0011

## **Optional Accessories**











Modell-Linie: F5L | F5LT2022

Showers | Manual shower

#### Flow controller 6.0 I/min

**2030027586** ESHHE0004

#### Flow controller 12.0 I/min

**2000104783** ESHHE0002


# Hygiene unit for F5L single lever mixer shower panel


**2030057065** ACLM2003 Shower gel dish for F5 shower panels made of stainless steel

**2030057077** ACXX2021










Housing extension for F5 shower panels made of stainless steel

**2030057066** ACXX2011 Housing extension for F5 shower panels made of stainless steel

**2030057067** ACXX2012 Housing extension for F5 shower panels made of stainless steel

**2030057068** ACXX2013 Housing extension for F5 shower panels made of stainless steel

**2030057069** ACXX2014



Housing extension for F5 shower panels made of stainless steel

**2030057070** ACXX2015

## **Spare Parts**









Modell-Linie: F5L | F5LT2022

Shower	s	Ма	nual	sł	יסו	W	er	

Flow controller 9,0 I/min	Rosette	Stainless steel care set				
<b>2000104782</b>	<b>2030048765</b>	<b>2000109019</b>				
ESHHE0001	ASET2006	ZWSPL0024				