


## **KWC** F5L-Therm

Stainless steel shower panel with hand shower fitting

## Modell-Linie: F5L | F5LT2023

Showers | Manual shower





## KWC-No.

## 2030066542

F5L-Therm stainless-steel shower panel for wall mounting with single-lever thermostat DN 15 and hand shower fitting kit. For connect ion to hot and cold water. Function block with integrated mixing cartridge and mechanism for an optional water hygiene unit for automatic water hygiene flushing, program-controlled thermal disinfection (additional bypass solenoid-operated flush valve cartridge necessary) and storage of statistical data. Thermostatically-controlled mixer cartridge with expansion element and active scald protection as well as adjustable and turn-proof temperature stop, and ceramic disc technology. All-metal construction, visible parts high-polished, chrome-plated. Pre-fitted chrome-plated brass shower rail with height-adjustable hand shower holder and chrome-plated brass hand shower, shower head with rain jet, diameter 110 mm, shower hose 900 mm. Housing made of stainless steel with raised function surface and cover caps made of plastic. With adjustable and lockable connections with backflow preventer and strainers.

Housing dimensions 235 x 1160 x 90 mm (W x H x D)

#### **Technical Data**

additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material casing	
material code casing	
material fitting	
minimum flow pressure	
type of mixing	
overall depth	
overall height	
overall width	
with rosettes/cover plate	

no	
yes	
no	
no	
not possible	
yes	
no	
manual	
yes	
prepared	
DN 15	
G 1/2 A	
Top section, ceramic	
stainless steel	
1.4301 Chrome Nickel steel V2A	
brass-look	
1 bar	
with thermostat	
90 mm	
1,160 mm	
235 mm	
yes	





## **KWC** F5L-Therm

Stainless steel shower panel with hand shower fitting

## Modell-Linie: F5L | F5LT2023

Showers | Manual shower

protective shutdown	no	
shower pipe draining	no	
with shower set	yes	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	yes	
type of mounting	wall mounting	
type of operation	manual operation	
type of shower	shower panel	
volume flow rate at 3 bar	0.15 l/s	
water connection	hose (gland nut)	
position of water connection	from top / backside	
with soap dish	no	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel-look	

#### **Optional Accessories**









Hygiene unit for F5L single lever mixer shower panel

2030057065 ACLM2003




Shower gel dish for F5 shower panels made of stainless steel

#### **2030057077** ACXX2021

¢

Housing extension for F5 shower panels made of stainless steel Housing extension for F5 shower panels made of stainless steel Housing extension for F5 shower panels made of stainless steel

#### **2030057066** ACXX2011



Housing extension for F5 shower panels made of stainless steel Housing extension for F5 shower panels made of stainless steel

## \_\_\_\_\_

**2030057067** ACXX2012



**KWC** F5L-Therm Stainless steel shower panel with hand shower fitting

# **Modell-Linie: F5L | F5LT2023** Showers | Manual shower

