


### Modell-Linie: F3E | F3ET2004

Showers | Electronic self closing shower





### KWC-No.

### 2030067170

F3E-Therm thermostatic mixer DN 15 as finished installation kit for wall mounting in mounting material, for shower facilities. Electrically controlled, connects to hot water and cold water. Function block with integrated solenoid valve cartidge and thermostat, with metal handle with adjustable and turn-proof temperature stop and option for manual thermal disinfection. All-metal construction, visible parts high-polished, chrome-plated. With holding frame and profile seal, stainless-steel cover plate  $190\times245$  mm with covered screw fixing including sensor with control electronics, rosette, backflow preventers and strainers. Depth adjustability 25 mm. Activated

hygiene flushing 24 hours after last activation and storage of statistical data. With option for parameterization and communication via optional, bidirectional remote control.

Either for battery operation with 6 V lithium battery (CR-P2) per fitting or separate power supply via power supply unit 6.75 V/12 V DC.

### Technical Data

Technical Data		
additional connections		
with backflow preventer		
Built-in fitting model		
calculation flow rate cold wat		
calculation flow rate hot wate		
circulation		
compatible A3000 open		
connection with pay water disp	·	
default automatic hygiene flus		
default flow time		
with filter		
adjustable flow time		
functional principle		
for hand shower		
hygiene flushing		
diameter nominal		
inlet size		
Locking mechanism		
material casing		
material fitting	·	
maximum flow time	·	
minimum flow pressure		

no		
yes		
Finishing section		
0.15 l/s		
0.15 l/s		
no		
no		
not possible		
24h after the last activity		
30 Seconds		
yes		
yes		
electronic self-closing		
no		
yes		
DN 15		
G 3/4 B		
Top section, non-ceramic		
stainless steel		
brass		
255 Seconds		
1 bar		











### Modell-Linie: F3E | F3ET2004


Showers | Electronic self closing shower

minimum flow time	1 Seconds	
type of mixing	with thermostat	
Parameterization	remote control	
power supply connection	6,75 / 12 V DC	
position of power connection	from top	
power consumption	1.5 Voltampere	
Type of power supply	Transformer	
with rosettes/cover plate	yes	
protective shutdown	yes	
shower pipe draining	no	
sound insulation	no	
surface finish casing	satin finished	
surface finish fitting	chromed	
surface treatment fitting	polished	
temperature limit	yes	
thermal disinfection	manual thermal disinfection	
with transformer/power supply	no	
type of mounting	in-wall installation with box	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of shower	in-wall fitting	
volume flow rate at 3 bar	0.23 l/s	
water connection	threaded connection (external)	
position of water connection	from side	
Accent colour	chrome-look (glossy)	
Basic colour	stainless steel	

# **Mandatory Accessories**









R3 system box for in-wall mixers

**2030036141** F3BX2001 R5 System box for in-wall mixer

**2030028990** F5BX2001 Extension cable 5 m

**2030043814** ACEX9010 Power supply unit

**2030039477** ACEX9001

# **Optional Accessories**



### Modell-Linie: F3E | F3ET2004

Showers | Electronic self closing shower







### Extension set

**2030067889** ACXT9001 Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005 2-button remote control for fittings F3 and F5

**2030036849** ACEX9004

### **Spare Parts**









### Cover

**2030048769** ASET2005 Temperature handle

**2030048766** ASET2004 Temperature stop

2030003296

## Solenoid valve cartridge

2030003033









## Holding frame

**2030045472** ASXX9004 Sensor, ID 12/00001

**2030048628** ASEX2001 Cover plate stainless steel

**2030048775** ASET2007

## Extension set

**2030067889** ACXT9001



Modell-Linie: F3E | F3ET2004 Showers | Electronic self closing shower





Cleaning product CHROMOL

**2000105091** ZWSPL0023

Stainless steel care set

**2000109019** ZWSPL0024