


## KWC F7E Electronic pillar tap

# Modell-Linie: F7 | F7EV1001 Taps | Electronic taps





#### KWC-No.

#### 3600001255

F7E pillar tap DN 15 for sanitary facilities, opto-electronically controlled. For connection to pre-mixed hot or cold water via hose and strainer. Control electronics, solenoid valve and sensor in and strainer. Control electronics, solenoid valve and sensor in stainless steel housing, brushed surface, outlet height 115 mm and projection 125 mm. Angle-adjustable and anti-theft aerator with integrated flow regulator 5.7 l/min. Activated water hygiene flushing 24 hours after last activation, safety switch-off with continuous reflection and saving of statistical data. With option for parameterization and communication via optional bidirectional remote control or C module with the necessary app. Optionally for battery operation with battery compartment including 6 V lithium battery (CR-P2) per fitting, for installation below the washbasin, or for separate power supply via power supply unit 6.75 V/12 V DC or AQUA 3000 open system accessories.

Battery compartment including battery or power supply unit with extension cable must be ordered separately.

#### **Technical Data**

with backflow preventer	
compatible A3000 open	
default automatic hygiene flus	
depressurised	
with filter	
functional principle	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
minimum flow pressure	
type of mixing	
Parameterization	
Pop-up waste set	
power supply connection	
position of power connection	
Type of power supply	
with rosettes/cover plate	
protective shutdown	
sound insulation	
Spout	
surface finish fitting	

no	
yes	
24h after the last activity	
no	
yes	
electronic self-closing	
yes	
DN 15	
G 3/8	
Top section, non-ceramic	
stainless steel	
1 bar	
no	
remote control	
no	
6,75 / 12 V DC / A3000 open	
from bottom	
other	
no	
yes	
no	
fixed	
brushed	













# KWC F7E Electronic pillar tap


# Modell-Linie: F7 | F7EV1001 Taps | Electronic taps

surface treatment fitting	brushed	
temperature limit	no	
thermal disinfection	no	
with transformer/power supply	no	
type of mounting	tap hole	
type of operation	sensor operation	
type of sensor	opto-electronic sensor	
type of tap	pillartap	
water connection	hose (gland nut)	
Accent colour	none	
Basic colour	stainless steel-look	

### **Mandatory Accessories**









### Battery compartment

**3600002063** ACEX9023

Power supply unit

**2030039477** ACEX9001

Extension cable 5 m

**2030043814** ACEX9010

Plug-in power supply unit

**3600002062** ACEX9022



#### In-wall power supply

**2030039825** ACEX9003

## **Optional Accessories**



# KWC F7E Electronic pillar tap

Modell-Linie: F7 | F7EV1001 Taps | Electronic taps



Bidirectional remote control for electronical fittings F3 and F5

**2030036654** ACEX9005



2-button remote control for fittings F3 and F5

**2030036849** ACEX9004



C module

**3600001331** ACEX9020



PURETHERM under-table thermostat

**2030012758** PURE0031

### **Spare Parts**



Hose

**2030041311** ASXX1005



Stainless steel care set

**2000109019** ZWSPL0024

Cleaning product CHROMOL

**2000105091** ZWSPL0023